

W-series reels are designed for extreme space-restricted applications. Perfect for under work bench mounting, can be mounted on ceiling or wall.

SUS Equipped with SUS protector

Stainless Steel protector has been added at hose outlet to extend life of outside casing.

Improved support strength

Strengthened bracket support arms more than twice of previous model.




Winner of Good Design Award in 2008.

Unique Frame Design for wall installation. New Standard of our TRIENS Brand.


Ceiling or Wall mount



Dimensions



Mounting Bracket dimensions (mm)



Air Hose Reels



Air Hose Reel **WHC-206** **65mm** **6m**
 •High quality polyurethane hose •Easy coupling

Air Hose Reel **WHC-303** **8.0mm** **3m**
 •High quality polyurethane hose

Model	Outlet Hose				MPa	Inlet Hose		Dimensions (mm)			Weight (kg)
	I.D. (mm)	m	Outlet	hose		m	Inlet	A	B	C	
WHC-206	6.5	6	Female G1/4	PU	1.4	0.8	Swivel fitting male R1/4	228	272	146	2.7
WHC-303	8.0	3	Female Rc3/8	PU	1.4	1.0	Swivel fitting male R3/8	228	272	146	2.8

comes with mounting base set

Outlet Cord Reels



Outlet Cord Reel **WCC-306** **100V** **220V** **6m**
 •Compact type triple outlet with a ground clip

Model	Outlet Cord			Power Rating		Inlet Cord		Dimensions (mm)			Weight (kg)
	Wire	m	Outlet			m	Inlet	A	B	C	
WCC-306A	1.25×3	6.1	outlet w/ground clip	AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	228	272	147	3.0

comes with mounting base set

Control Switch Reel



Control Switch Reel **WPC-406** **4 cores** **6m**

Model	Outlet Cord			Power Rating		Inlet Cord		Dimensions (mm)			Weight (kg)
	Wire	m	Outlet			m	Inlet	A	B	C	
WPC-406	2.0×4	6	soldered wires	AC125V/6A	AC250V/5A	0.8	Bullet terminal	228	272	147	3.1

Comes with mounting base set

W-series

Unique Design with innovative level wind mechanism

Extreme compact width and height compared to previous models

Robust supporting arms are especially designed for wall mounting position

A new streamlined design that symbolizes the series

Introduces a level wind mechanism that prevents tangling


Ceiling or wall mount available




Ceiling or Wall mount




60 Degrees pivoting



Dimensions



Mounting Bracket dimensions



Air Hose Reels



Air Hose Reels
WHS-215 6.5 mm **15m**
WHS-310 8.0 mm **10m**

Anti-spark Hose Reels
WHS-215S 6.5 mm **15m**
WHS-310S 8.0 mm **10m**

Model	Outlet Hose		MPa	Inlet Hose		Dimensions (mm)			Weight (kg)		
	I.D. (mm)	m		Outlet	hose	m	Inlet	A		B	C
WHS-215	6.5	15	Female G1/4	PU	1.4	0.8	Swivel Fitting Male R1/4	325	300	214	8.6
WHS-310	8.0	10	Female Rc3/8	PU	1.4	1.0	Swivel Fitting Male R3/8	325	300	214	8.7
WHS-215S	6.5	15	Female G1/4	Anti-spark	1.4	0.8	Swivel Fitting Male R1/4	325	300	214	8.6
WHS-310S	8.0	10	Female Rc3/8	Anti-spark	1.4	1.0	Swivel Fitting Male R3/8	325	300	214	8.7

comes with mounting base set

Outlet Cord Reels



Outlet Cord Reels
WCS-315 100V 220V **15m**

• Compact type triple outlet with a ground clip

Model	Outlet Cord		Power Rating		Inlet Cord		Dimensions (mm)			Weight (kg)
	Wire	m	Outlet		m	Inlet	A	B	C	
WCS-315	2.0×3	15	outlet w/ground clip	AC125V/6A AC250V/6A	0.8	plug (w/ground clip)	325	300	214	9.2

comes with mounting base set